# O T T 28 230V

#### **ONYX 28 230V**



## **ONYX28**Features

#### **Standard**

- XL Light
- Digital Display
- 4-Speed Body Fan
- Easy-Access Timer
- Easy Acrylic Removal System
- Turbo Cooling System
- Programmable Internal Timer
- Dual Hour Counters
- TMAX Compatible

### **Optional**


- Pre-Installed Speakers
- MyMp3
- TMAX Integrated








## **Dimensions**







Onyx 28

Model Number Canopy Lamps Bench Lamps Facial Tanning Electrical Rating

Power Requirements
Buckbooster
AC Requirements
Session Time
Dimensions
Recommended Room Size
Shipping Weight

28

14 x 110W R-UVA 14 x 100W R-UVA

N/A

230V ~17A 60Hz

2 Pole (2 Hots 1 Ground)

25 Amp

0.50 Kva

BTU 6000

20 Minutes

83"L x 35"W x 47"H

8 ft. x 7 ft.

425 lbs.



REQUIRED: A 230V - 20 Amp outlet is needed when operating this tanning equipment.



DISCLAIMER: A 110V outlet is needed when operating equipment with external T-max system or MP3 System

Note: Equipment comes standard in three phase configuration. Buck boosters must be installed by licensed electrician in your state/county



800.874.2776 • Sales@prosun.com • ProSun.com • 2442 23rd St. N. St. Petersburg, FL 33713 510(K): K181455 \*ProSun reserves the right to change design and specifications without notice.