



42XLc High Intensive 230V



V3 Features

Standard

- XL Light
- Digital Display
- 4-Speed Body Fan
- Easy-Access Timer
- Easy Acrylic Removal System
- Turbo Cooling System
- Programmable Internal Timer
- Dual Hour Counters
- TMAX Compatible

Optional

- TMAX Integrated



ProSun V3 42 XLc High Intensive

Model Number

42V3

Lamps

42 x 160W R-UVA XL

Electrical Rating

230V ~32A 60 Hz
2 Pole (2 Hots 1 Ground)

Power Requirements

40 Amp

Buckbooster

1.0 Kva

AC Requirements

A/C 6000 BTU

Session Time

10 Minutes

Dimensions

83" H x 60"D



Recommended Room Size

8 ft. x 6 ft.

Shipping Weight

550 lbs.

Dimensions



110V

DISCLAIMER: A 110V outlet is needed when operating equipment with external T-max system.



230V

REQUIRED: A 230V outlet is needed when operating this tanning equipment.

Note: Equipment comes standard in three phase configuration. Buck boosters must be installed by licensed electrician in your state/county



800.874.2776 • Sales@prosun.com • ProSun.com • 2442 23rd St. N. St. Petersburg, FL 33713

510(K): K181455 *ProSun reserves the right to change design and specifications without notice.

Contraindication: This product is contraindicated for use on persons under the age of 18 years. "Contraindication: This product must not be used if skin lesions or open wounds are present." "Warning: This product should not be used on individuals who have had skin cancer or have a family history of skin cancer." "Warning: Persons repeatedly exposed to UV radiation should be regularly evaluated for skin cancer.