

36 SLi High Intensive 230V





Standard

- XL Light
- Ambient FlowLight
- DecoLight
- QuickStart Function
- Digital Timer Display
- Adjustable Body Cooling
- Stand-by Inside Lighting
- Programmable Internal Timer
- Dual Hour Counters
- TMAX Compatible
- Pre-Installed Speakers
- MyMp3

Optional

- TMAX Integrated
- Facial Cooler



Model Number
Canopy Lamps
Bench Lamps
Facial Lamps
Electrical Rating

Power Requirements
Buckbooster
Session Time
AC Requirements
Dimensions
Recommended Room Size
Shipping Weight

36X-P

20 x 160W R-UVA 16 x 180W R-UVA

3 x 400W

230V 3~22A 60 Hz

3 Pole (3 Hots 1 Ground)

30 Amp

2 * .75 Kva

12 Minutes


BTU 6000 A/C


90.16"L x 47.64"W x 59"H

8 ft. x 9 ft.


675 lbs.

Dimensions









Note: Equipment comes standard in three phase configuration. Buck boosters must be installed by licensed electrician in your state/county



800.874.2776 • Sales@prosun.com • ProSun.com • 2442 23rd St. N. St. Petersburg, FL 33713 510(K): K181455 *ProSun reserves the right to change design and specifications without notice.