

38 SLi High Intensive 230V



X5Features


Standard


- XL Light
- Ambient FlowLight
- QuickStart Function
- Touch Screen Display
- Smart Touch Control
- Adjustable Cooling
- Facial Cooling
- Contour Acrylic
- Stand-by Inside Lighting
- Programmable Internal Timer
- Dual Hour Counters
- TMAX Compatible
- Pre-Installed Speakers

Optional

- MyMp3
- SoundAround Plus
- Bluetooth
- SmartVoice Guide
- Studio/Wellness Music
- TMAX Integrated
- XSens Aromatherapy
- QSens Cooling Mist

Dimensions







Model Number Canopy Lamps Bench Lamps Facial Lamps Electrical Rating

Buckbooster
Session Time
AC Requirements
Dimensions
Recommended Room Size
Shipping Weight

Power Requirements


38X 22 x 160W R-UVA 16 x 180W R-UVA 3 x 400W 230V 3~25A 60Hz

3 Pole (3 Hots 1 Ground)

40 Amp 2 x 1.0 Kva 12 Minutes

BTU 9000 90.16"L x 53.5"W x 61.4"H

9 ft. x 9 ft. 975 lbs.



Note: Equipment comes standard in three phase configuration. Buck boosters must be installed by licensed electrician in your state/county



800.874.2776 • Sales@prosun.com • ProSun.com • 2442 23rd St. N. St. Petersburg, FL 33713 510(K): K181455 *ProSun reserves the right to change design and specifications without notice.