




	LUXURA X10 SPECIFICATIONS	52 SLI HIGH INTENSIVE IP
	CANOPY LAMPS	ULTRA INTENSIVE 30 X 200 WATTS IP
	BENCH LAMPS	ULTRA INTENSIVE 22 X 200 WATTS IP
	FACIAL LAMPS	4 X 520 WATTS
	BREAKER	3 PHASE: 40 AMP
	BUCKBOOSTER	2 POLE 220V ( 2 HOTS 1 GROUND, NEUTRAL NEEDED FOR AC) 3 PHASE: 2*1.0 KVA
	ROOM AC REQUIREMENTS	BTU 12,000 A/C (TONS) 1
	SESSION TIME	10 MINUTES
	PROGRAMMABLE INTERNAL TIMER	STANDARD
	DUAL HOUR COUNTERS	STANDARD
	LCD TIMER DISPLAY	STANDARD
	TMAX COMPATIBLE	COMPATIBLE
	PRE-INSTALLED SPEAKERS	STANDARD
	STUDIO/WELLNESS MUSIC	STANDARD
	SOUNDAROUND PLUS	STANDARD
	MYMP3 INTEGRATED	STANDARD
	QSENS COOLING MIST	OPTIONAL
	XSENS AROMATHERAPY	OPTIONAL
	CLIMAX COOLING	STANDARD
	AMBIENT FLOWLIGHT	STANDARD
	CONTOUR PLUS	STANDARD
	HPS FACIAL TANNING FILTER	STANDARD
	BLUETOOTH	STANDARD
	ADMO EXPERIENCE CONTROL PANEL	STANDARD
	XL LAMPS	STANDARD
	IP CONTROL	STANDARD
	DIMENSIONS	91.4"D X 56.7"W X 80.7"H
	RECOMMENDED ROOM SIZE	10 FT. X 9 FT.
	SHIPPING WEIGHT	1,425 LBS.

